MIWE TKL

MIWE



Start small and grow little by little.

Pastry shops and small bakeries often prefer to freeze and store their products right on the baking trays. The MIWE TKL deep-freeze bay storage system is the ideal solution for this. This gem can be expanded by two additional bays if demand increases, making it a safe investment for the future.

You will reap the benefits immediately:

At a glance:

- Pastries, dough pieces, baked and half-baked products can be frozen and stored on trays without much effort.
- Flexible and future-proof: the MIWE TKL deep-freeze bay storage system is modularly expandable and features a multifunctional compartment with automatically adjustable fins for defined distribution of the refrigerating power (75% of the refrigerating power for flash freezers).
- Separate spaces are ideal for preserving a wide variety of products and also for preventing high losses of coldness. Two to eight variable storage chambers can be used to store up 12 60/80 baking trays.
- New door system without a handle: magnets close the chambers tightly and reliably. The smooth surface makes for easy cleaning.
- User-friendly: the easy-to-use fixed program control MIWE FP8 offers MIWE remote functionality.

MIWE TKL

- High machine power thanks to robust and high-performance refrigeration unit. The cooling system guarantees short cooling times with little air movement and very high relative humidity despite low temperatures.
- The refrigeration system, which is powered by the environmentally friendly ester oil refrigerant R449A, is equipped with high-pressure and low-pressure sensors, high-performance evaporators with large evaporator surfaces, speed-controlled evaporator ventilation and electric defrosting.
- Energy-saving: the insulation made up of 100mm polyurethane rigid foam prevents energy losses and keeps the goods chilled in the event of a power cut.
- High-quality design: the walls are made of robust galvanized sheet steel (optionally stainless steel) coated in particularly hygienic plastic (RAL 9002).
- The feet can be adjusted to all floor conditions.

Technical data	TKL 1.2	TKL 1.4	TKL 1.6
Temperature range °C	-25 to -10	-25 to -10	-25 to -10
Relative humidity % RH	High	High	High
Product state	Unproofed, proofed	Unproofed, proofed	Unproofed, proofed
Refrigerating capacity*	2090W	3000W	3000W
Refrigerant	R449A	R449A	R449A
Baking tray size**	60/80	60/80	60/80
Number of trays	36	60	84
Evaporator fin spacing mm	7mm	7mm	7mm
Insulation mm	100	100	100
Control system	FP8	FP8	FP8
Connected load kW***	2,6	3,1	3,1
Max. operating current A	7,1	9,9	10,2

* -25°C VT/+40°C KT

**Further tray sizes available on request

***Voltage 400/230V; 3 N/PE 50Hz