

# MIWE GVAS



## At a glance



- ▶ Capacity: 20 trays (DIN 58/78 cm) or 40 trays (DIN 60/40 cm).
- ▶ Level spacing: 60 mm with 20 supports.
- ▶ Support capacity can be varied widely through freely selectable spacing – there is also sufficient space for large-volume pastry products or bread baskets.
- ▶ The convenient, easy-to-use MIWE FP8 fixed programme control: all process steps (SA, GU, GV, GÄ, AS) can be individually selected or stored as complete programmes for controlling processes (a maximum of 5 days off can be set).
- ▶ The proofing process can be started, interrupted and continued at any time, and the intelligent control system always calculates the ideal processing time.
- ▶ Automatic restart after a power failure (proofing process is continued).
- ▶ Energy-saving: no additional electric heating system needed thanks to passive evaporation of condensation water.
- ▶ Easy to use and secure: easy-to-clean door with a continuous handle closes automatically and is available with your choice of hinges on the right or left.
- ▶ Magnet seal is removable to allow for easy replacement when dirty or damaged.
- ▶ Feet can be adjusted to all floor conditions.
- ▶ The exterior panels are made of robust, brushed stainless steel, and the interior is made of hygienic, polished stainless steel.
- ▶ 60 mm of insulation saves energy and provides extra „insurance“ in the case of a power cut.
- ▶ Comes ready for immediate use.

## Technical data

	<b>GVAS</b>
Exterior dimensions in cm (W x D x H)	74x105x206
Temperature range °C	-12 to +35
Refrigerating capacity W	906
Refrigerant	R 404 A, CFC-free
Evaporation temperature °C	-25
Condensation temperature °C	+40
Capacity l	900
Connected load W	1,000
Maximum operating current A	5,3
Voltage	230 V; 1/N/PE; 50 Hz